LAZY DAZE MOTORHOMES 2004 FEATURES AND SPECIFICATIONS

S = Standard Equipment O = Optional Equipment = Not Available CHASSIS FEATURES	23%'REAR LOUNGE	231/2 TWIN-KING BED	23% FRONT DINETTE	23% FRONT LOUNGE	26½ REAR KITCHEN	26½' MID BATH	26%' REAR BATH	26%'ISLAND BED	30' ISLAND BED
Ford E-450 super duty chassis with 158" wheel base and 4.56 ratio wider rear axle.	S	S	S	S					
Ford E-450 super duty chassis with 176" wheel base and 4.56 ratio wider rear axle.					S	S	S	S	
Ford E-450 super duty chassis with 211" wheel base and 4.56 ratio wider rear axle.									S
305 horse power, fuel injected V-10 engine with upgraded 4R100 electronic 4 speed overdrive transmission.	S	s	S	S	s	S	s	S	s
4 wheel disc brakes with ABS (anti-lock braking system).	S	S	S	S	S	Ø	Ø	S	S
Steel belted radial tires with stainless steel wheel covers and full sized spare tire.	S	S	S	S	S	S	S	S	S
Single 55 gallon gasoline tank.	S	S	S	S	S	S	S	S	S
130 amp heavy-duty alternator.	S	S	S	S	S	S	S	S	S
Lazy Daze designed integrated running boards and front fender flares.	S	S	S	S	S	S	S	S	S
Low profile mirrors that can fold in backward or forward.	S	S	S	S	S	S	S	S	S
Tow package with 2" receiver hitch or ball hitch.	S	S	S	S	S	S	S	S	S
Windshield boot that covers the outside three front cab windows for improved insulation and dash board sun protection.	S	S	S	S	S	S	S	S	s
Tachometer, A/B digital trip odometer, all gauges, intermittent windshield wipers, tilt steering wheel and cruise control.	S	S	S	S	S	S	S	S	S
Power operated tinted windows and power door locks.	S	S	S	S	S	S	S	S	S
High output factory installed dash air conditioning (Not after market).	S	S	S	S	S	S	S	S	S
High back driver and passenger reclining seats with matching interior upholstery and lumbar adjustments, dual air bags, and automatic seatbelt tensioners.	S	S	S	S	S	S	S	S	s
Six way power drivers seat.	S	S	S	S	S	S	S	S	S
Beverage holders for driver and front passenger.	S	S	S	S	S	S	S	S	S
Insulated and carpeted cab floor and engine cover for reduced heat and noise.	S	S	S	S	S	S	S	S	S
AM, FM, stereo in-dash single C.D. with infrared multi-function remote control (no cassette).	S	S	S	S	S	S	S	S	S
AM, FM, stereo in-dash cassette, and remote mounted 10 disc C.D. (MP3) changer with infrared multi-function remote control.	0	0	0	0	0	0	0	0	0
Remote mounted 40 channel C.B. with weather channels and roof mounted antenna.	0	0	0	0	0	0	0	0	0
Hardwood dashboard trim.	0	0	0	0	0	0	0	0	0
Faux gray leather cab seats.	0	0	0	0	0	0	0	0	0
Bilstein high performance gas shock absorbers. Not needed or recommended with 23½' models.					0	0	0	0	0
6.0 L Power Stroke turbo diesel engine and Torqshift 5-speed automatic transmission.					0	0	0	0	
INTERIOR COACH FEATURES									
Molded kitchen counter top with raised edges and attractive granite finish.	S	S	S	S	S	S	S	S	S
Matching molded kitchen counter top drop leaf extension.	S	S	S	S		S	S		S
Easy maintenance acrylic double kitchen sink with formica over-laid sink cover.	S	S	S	S	S	S	S	S	S
Single handle kitchen faucet with pull out spout and adjustable spray.	S	S	S	S	S	S	S	S	S
Built in pantry with adjustable shelves.					S	S	S	S	S
Built in coffee maker.									S
High quality decorative linoleum flooring in kitchen areas.	S	S	S	S	S	S	S	S	S
High output microwave with touch pad controls, turntable, and easy access height.	S	S	S	S	S	S	S	S	S
Power exhaust range hood that contains a full systems monitor panel read out for sewage tank, gray tank, fresh water tank, LP gas tank, house batteries condition, as well as the water pump switch, water heater switch, generator start/stop switch and hour meter.	Ø	S	S	Ø	S	S	S	S	S
Three-burner range with piezo direct ignition igniter, high output burner, bi-fold stove cover and an oven.	S	S	S	S	S	S	S	S	S

INTERIOR COACH FEATURES CONTINUED	23%'REAR LOUNGE	23%' TWIN-KING BED	231/2' FRONT DINETTE	23%' FRONT LOUNGE	26½' REAR KITCHEN	26½' MID BATH	26½' REAR BATH	26½'ISLAND BED	30' ISLAND BED
Electronic ignition water heater with convenient "in operation" indicator light located on the systems monitor panel.	S	S	S	s	S	s	S	S	S
20,000 BTU wall furnace with electronic ignition, low amp draw motor and heat ducts.	S	S	S	S	S	S	S	S	
30,000 BTU wall furnace with electronic ignition and multiple heat ducts.	+	 		<u> </u>	Ť	Ť			S
Dometic 6' two-door refrigerator with adjustable thermostat and automatic switch over gas/electric operation.	S	S	S	S	S	S	S	S	
Dometic 8' two-door refrigerator with adjustable thermostat, ice maker and automatic switch over gas/electric operation. The ice maker can be deleted for credit, if desired.									s
Shower, bath area includes: Large mirror, medicine cabinet, isolated dressing room, one piece molded shower stall and hand wash basin.	S	S	S	S	s	S	S	S	s
Single handle wash basin faucet.			S	S	S	S	S	S	S
Residential size porcelain toilet with convenient basin hand spray rinse attachment.	S	S	S	S	S	S	S	S	S
Decorative linoleum flooring in bathroom area.	S	S	S	S	S	S	S	S	S
SHURflo "Extreme" 5.7 electronic variable speed, high output water pump.	S	S	S	S	S	S	S	S	S
High output 12V variable speed, reverse direction Fan-tastic ceiling fan with thermostat control.	S	S	S	S	S	S	S	S	S
Numerous incandescent lights, and up to seven twin tube recessed fluorescent lights.	S	S	S	S	S	S	S	S	S
45 amp electronic solid state converter with high output house battery charger.	S	S	S	S	S	S	S	S	S
Many high quality drawers mounted on ball bearing guides (up to 11).	S	S	S	S	S	S	S	S	S
Real wood interior cabinetry with new California maple finish. Not pressed wood.	S	S	S	S	S	S	S	S	S
Pleated "black out" night shades with valance surround.	S	S	S	S	S	S	S	S	S
Sofa cushions and permanent mattress beds constructed with multi-density, high quality foam wrapped in Dacron.	S	S	S	S	S	S	S	S	S
Cab-over mattress folds over and out of the way for easy access to the front cab seats. A ladder is included for easy access to the cab-over bed.	S	S	S	S	S	S	S	S	
High density low profile carpet with padding in non-kitchen living areas.	S	S	S	S	S	S	S	S	S
Entertainment center built in to the cab-over area above the passenger/driver seats, which includes: large inside storage compartments and a 20" LCD flat screen stereo TV. This design still allows you to enter in an up-right position and sit down on either of the front cab seats.			0	0	0		0	0	s
Single pedestal game table that stores in wardrobe. Table size 21" X 36".					0	0	0		
Telephone jack.	S	S	S	S	S	S	S	S	S
12 volt outlet in coach.	S	S	S	S	S	S	S	S	S
TV stand, with 120 volt and 12 volt TV antenna outlets furnished for your TV.	S	S	S	S					
Built-in 12 volt 15" LCD flat screen stereo TV with infrared remote control.					S	S	S	S	
Built-in 12 volt 20" LCD flat screen stereo TV with infrared remote control.									S
13,500 B.T.U. low profile refrigerated roof air.	S	S	S	S	S	S	S	S	
Heavy duty 15,000 B.T.U. refrigerated roof air.					0	0	0	0	S
Integrated heat strip within roof air conditioner that produces 5,000 B.T.U. of warmth.	S	S	S	S	S	S	S	S	S
Additional safety features include: Smoke alarm, propane gas detector, carbon monoxide alarm, fire extinguisher, up to 8 emergency exits and flame retardant interiors.	s	s	s	s	s	s	s	s	s
EXTERIOR COACH FEATURES									
Smooth exterior polyurethane laminated aircraft aluminum coach body panels that are durable, lighter weight and replaceable. Aluminum is non-flammable, unlike fiberglass, and offers superior appearance, and outstanding endurance. A Lazy Daze exclusive.	s	S	s	S	s	s	S	s	s
One piece painted aluminum roof that is U.V. resistant unlike rubber or non-painted fiberglass.	S	S	S	S	S	S	S	S	S
Coach exterior is painted with durable, easy to maintain polyurethane (Imron type) paint. It is not prone to yellowing or chalking as is unpainted fiberglass, which is commonly used in the industry.	S	S	S	s	s	S	S	S	S
Streamline one-piece molded nose cone with no real front windows for improved aerodynamics, insulation, appearance and reliability.	S	S	S	S	S	S	S	s	S
Unitized cab to cab-over (no gap) for reduced wind resistance.	S	S	S	S	S	S	S	S	S
Exterior streamline radius corners (not square).	S	S	S	S	S	S	S	S	S
Low profile silhouette for improved handling and fuel economy.	S	S	S	S	S	S	S	S	S
Hinged skirts that partially covers the rear dual wheels for improved aerodynamics and easy access to the tires. A Lazy Daze exclusive.	S	S	s	s	s	s	s	s	s

Attractive molded spare tire cover that is integrated into the rear coach wall. The spare tire is not stored behind this over on all models. Entire coach body floor, walls and ceiling contain 2½" insulation. \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$	EXTERIOR COACH FEATURES CONTINUED	23%'REAR LOUNGE	23½' TWIN-KING BED	23%' FRONT DINETTE	23½' FRONT LOUNGE	26%' REAR KITCHEN	26½' MID BATH	26½' REAR BATH	261/21SLAND BED	30' ISLAND BED
Enfire coach body floor, walls and reliling contain 2½' insulation. \$ S S S S S S S S S		S	S	S	S	S	S	S	S	s
25 foot 30 amp exterior power cord that detaches from motorhome body for added convenience. S S S S S S S S S		S	S	S	S	S	S	S	S	S
Conan AKW microquiet gasoline generator. Causility coach entry door with radius top corners, dead bolt, screen door, window and roller stade. S S S S S S S S S S S S S S S S S S S			-							_
Coublity coach entry door with radius top comers, dead bolt, screen door, window and roller shade. Interior entry step light and exterior amber porch light. Large double pane, thermal (approx. ½ inch space between panes) windows surrounding the cache that are linked, anti-glae safety glass and offer privacy during the day. Fender wells and underbelly pan are covered with galvanized steel. Fender wells and underbelly pan are covered with galvanized steel. Fender wells and underbelly pan are covered with galvanized steel. Fender wells and underbelly pan are covered with galvanized steel. Fender wells and underbelly pan are covered with galvanized steel. Fender wells and underbelly pan are covered with galvanized steel. Fender wells and underbelly pan are covered with galvanized steel. Fender wells and underbelly pan are covered with galvanized steel. Fender wells and underbelly pan are covered with galvanized steel. Fender wells and underbelly pan are covered with galvanized steel. City water exterior hook up and includes a brass pressure regulator. City water exterior hook up and includes a brass pressure regulator. City water exterior hook up and includes a brass pressure regulator. City water exterior hook up and includes a brass pressure regulator. City water exterior hook up and includes a brass pressure regulator. City water exterior hook up and includes a brass pressure regulator. S S S S S S S S S S S S S S S S S S S			S			S	S		S	
Large double pane, thermal (approx. ¼ inch space between panes) windows surrounding the casch that are linted, anti-glare safety glass and offer privacy during the day. Fender wells and underbeitly pan are covered with galvarized steel. Large radius outside lockable compartments for: Folding chairs, B.B.Q., leveling blocks, fishing poles, golf clubs, etc. The 26% Island Bed and 30 Island bed can also accommodate skis within \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$	Quality coach entry door with radius top corners, dead bolt, screen door, window and roller	s	S	S	S	S	S	S	S	S
coach that are timed, anti-glare safety glass and offer privacy during the day. Fender wells and underbelly pan are covered with galvanized steel. Large radius cutside lockable compartments for: Folding chairs, B.B.Q., leveling blocks, fishing ploses, gold tolks, etc. The 26% leant Bed and 30° Island bed can also accommodate skis within S.	Interior entry step light and exterior amber porch light.	S	S	S	S	S	S	S	S	S
Large radius outside lockable compartments for, Folding chairs, B.B.D., leveling blocks, fishing poles, golf tolubs, etc. The 28% Island Bed and 30 Island bed can also accommodate skis within the 8' long rear exterior accessible compartment. City water exterior hook up and includes a brass pressure regulator. Convenient separate storage compartment for supplied 15' sewage hose. S S S S S S S S S S S S S S S S S S S		S	S	S	S	S	S	S	S	S
poles, golf clubs, etc. The 26½ Island Bed and 30 Island bed can also accommodate skis within its 8¹ long rear exterior accessible compartment. S	· ·	S	S	S	S	S	S	S	S	S
Convenient separate storage compartment for supplied 15' sewage hose. Roof rack and ladder. S S S S S S S S S S S S S S S S S S S	poles, golf clubs, etc. The 261/2' Island Bed and 30' Island bed can also accommodate skis within	S	S	S	S	S	S	S	S	s
Roof rack and ladder. Sleek aerodynamic awning. Fabric and legs are stored within an aluminum housing, when closed, for maximum longevity. One person from the ground can easily operate awning. Three-battery system. One 12V chassis battery separated, with a solid state isolator, from two followers. One to 12V chassis battery separated, with a solid state isolator, from two followers. One to 12V chassis battery separated, with a solid state isolator, from two followers. One to 12V chassis battery separated, with a solid state isolator, from two followers. One to 12V chassis battery separated maximum performance and longevity. Separate molded plastic exterior coach battery compartment for low maintenance and slide out battery tray for easy battery service. Separate molded plastic exterior coach battery compartment for low maintenance and slide out battery tray for easy battery service. Separate molded plastic exterior coach battery compartment for low maintenance and slide out battery tray for easy battery service. Separate molded plastic exterior coach battery compartment for low maintenance and slide out battery tray for easy battery service. Mapplified Winegard TV antenna with booster and outside cable hook-up. Separate molded plastic exterior coach battery service. Manual or automatic search digital satellite antenna. O O O O O O O O O O O O O O O O O O O	City water exterior hook up and includes a brass pressure regulator.	S	S	S	S	S	S		S	S
Size Aerodynamic awning. Fabric and legs are stored within an aluminum housing, when closed, for maximum longevity. One person from the ground can easily operate awning. Three-battery system. One 12V chassis battery separated, with a solid state isolator, from two 6V-coach batteries (wired in series to produce 12 volts) for maximum performance and longevity.										
closed, for maximum longevity. One person from the ground can easily operate awning. S S S S S S S S S		S	S	S	S	S	S	S	S	S
EV-coach batteries (wired in series to produce 12 volts) for maximum performance and longevity.	closed, for maximum longevity. One person from the ground can easily operate awning.	S	S	S	S	S	S	S	S	S
battery tray for easy battery service.	6V-coach batteries (wired in series to produce 12 volts) for maximum performance and longevity.	S	S	S	S	S	S	S	S	S
Moon roof hatch. A large screened opening vent above the cab-over bed, for improved ventilation, easy entry to the roof and furnishes another safety escape exit for those sleeping in the cab-over bed. This hatch is deleted when the entertainment center is installed. Solar panel with digital read out charge controller.	battery tray for easy battery service.									
ventilation, easy entry to the roof and furnishes another safety escape exit for those sleeping in the cab-over bed. This hatch is deleted when the entertainment center is installed. Solar panel with digital read out charge controller.		S	S	S	S	S	S	S	S	S
Manual or automatic search digital satellite antenna.	ventilation, easy entry to the roof and furnishes another safety escape exit for those sleeping in	s	s	s	s	S	S	s	S	
Electric coach entry step.	Solar panel with digital read out charge controller.	0	0	0	0	0	0	0	0	S
Back up camera with visor mounted 5" LCD color monitor.	Manual or automatic search digital satellite antenna.	0	0	0	0	0	0	0	0	0
Outside shower with insulated door.	Electric coach entry step.	0	0	0	0	0	0	0	0	S
Polyurethane insulation on holding tanks.	Back up camera with visor mounted 5" LCD color monitor.	0	0	0	0	0	0	0	0	0
Sealed 12V house battery disconnect switch.	Outside shower with insulated door.	0	0	0	0	0	0	0	0	S
Choice of interior color schemes in teal-brown, brown or blue.	·	0	0	0	0	0	0	0	0	0
Choice of interior color schemes in teal-brown, brown or blue.	Sealed 12V house battery disconnect switch.	0	0	0	0	0	0	0	0	0
Choice of exterior accent colors in two-tone teal, brown, blue, red or silver. S S S S S S S S S		0	0		0	0	0	0	0	
COACH SPECIFICATIONS LIQUIDS CAPACITIES (GALLONS) 50 50 60 60 58 60 50 60 Approximate total fresh water. 50 50 60 60 58 60 50 60 Approximate gray water storage. 24 24 24 28 30 28 24 28 30 28 24 28 30 28 24 28 30 28 24 28 30 28 24 28 30 28 24 28 30 28 24 28 30 28 24 28 30 28 24 28 30 28 24 28 30 28 24 28 30 28 24 28 30 28 24 28 30 28 24 28 30 28 24 28 30 28 24 28 30 28 24 28 30	, , , , , , , , , , , , , , , , , , ,									
Approximate total fresh water. 50 50 60 60 58 60 50 60		3	3	3	3	٥	3	3	3	3
Approximate total fresh water. 50 50 60 60 58 60 50 60	LIQUIDS CAPACITIES (GALLONS)									
Approximate sewage storage. Electronic ignition water heater. Fropane tank (rated tank capacity). COACH DIMENSIONS (INCHES) Approximate exterior unladen coach height from ground to top of roof air. Add 2" to the 26½' models when equipped with the optional 15,000 BTU roof air. NOTE: 23½' models sit higher due to their lighter weight combined with the E-450 chassis. Exterior coach width (add an additional 9" per side for the fold-in cab mirrors). Bumper to bumper coach length. Add 2" for the rear exterior spare tire cover and an additional 2" The state of the sewage storage. 24		50	50	60	60	60	58	60	50	60
Electronic ignition water heater. Propane tank (rated tank capacity). COACH DIMENSIONS (INCHES) Approximate exterior unladen coach height from ground to top of roof air. Add 2" to the 26½' models when equipped with the optional 15,000 BTU roof air. NOTE: 23½' models sit higher due to their lighter weight combined with the E-450 chassis. Exterior coach width (add an additional 9" per side for the fold-in cab mirrors). Bumper to bumper coach length. Add 2" for the rear exterior spare tire cover and an additional 2" Electronic ignition water heater. 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6	Approximate gray water storage.	24	24	32	32	35	35	35	35	35
Propane tank (rated tank capacity). COACH DIMENSIONS (INCHES) Approximate exterior unladen coach height from ground to top of roof air. Add 2" to the 26½' models when equipped with the optional 15,000 BTU roof air. NOTE: 23½' models sit higher due to their lighter weight combined with the E-450 chassis. Exterior coach width (add an additional 9" per side for the fold-in cab mirrors). Bumper to bumper coach length. Add 2" for the rear exterior spare tire cover and an additional 2" Bumper to bumper coach length. Add 2" for the rear exterior spare tire cover and an additional 2" Bumper to bumper coach length. Add 2" for the rear exterior spare tire cover and an additional 2" Bumper to bumper coach length. Add 2" for the rear exterior spare tire cover and an additional 2" Bumper to bumper coach length. Add 2" for the rear exterior spare tire cover and an additional 2" Bumper to bumper coach length. Add 2" for the rear exterior spare tire cover and an additional 2" Bumper to bumper coach length. Add 2" for the rear exterior spare tire cover and an additional 2" Bumper to bumper coach length. Add 2" for the rear exterior spare tire cover and an additional 2" Bumper to bumper coach length. Add 2" for the rear exterior spare tire cover and an additional 2" Bumper to bumper coach length. Add 2" for the rear exterior spare tire cover and an additional 2" Bumper to bumper coach length. Add 2" for the rear exterior spare tire cover and an additional 2" Bumper to bumper coach length. Add 2" for the rear exterior spare tire cover and an additional 2" Bumper to bumper coach length. Add 2" for the rear exterior spare tire cover and an additional 2" Bumper to bumper coach length. Add 2" for the rear exterior spare tire cover and an additional 2" Bumper to bumper coach length. Add 2" for the rear exterior spare tire cover and an additional 2" Bumper to bumper coach length. Add 2" for the rear exterior spare tire cover and an additional 2" Bumper to bumper coach length. Add 2" for the rear exterior spare tire	Approximate sewage storage.	24	24	28	28	30	28	24	28	30
COACH DIMENSIONS (INCHES) Approximate exterior unladen coach height from ground to top of roof air. Add 2" to the 26½' models when equipped with the optional 15,000 BTU roof air. NOTE: 23½' models sit higher due to their lighter weight combined with the E-450 chassis. Exterior coach width (add an additional 9" per side for the fold-in cab mirrors). Bumper to bumper coach length. Add 2" for the rear exterior spare tire cover and an additional 2" Bumper to bumper coach length. Add 2" for the rear exterior spare tire cover and an additional 2" Bumper to bumper coach length. Add 2" for the rear exterior spare tire cover and an additional 2" Bumper to bumper coach length. Add 2" for the rear exterior spare tire cover and an additional 2" Bumper to bumper coach length. Add 2" for the rear exterior spare tire cover and an additional 2" Bumper to bumper coach length. Add 2" for the rear exterior spare tire cover and an additional 2" Bumper to bumper coach length. Add 2" for the rear exterior spare tire cover and an additional 2" Bumper to bumper coach length. Add 2" for the rear exterior spare tire cover and an additional 2" Bumper to bumper coach length. Add 2" for the rear exterior spare tire cover and an additional 2" Bumper to bumper coach length. Add 2" for the rear exterior spare tire cover and an additional 2" Bumper to bumper coach length. Add 2" for the rear exterior spare tire cover and an additional 2" Bumper to bumper coach length. Add 2" for the rear exterior spare tire cover and an additional 2" Bumper to bumper coach length. Add 2" for the rear exterior spare tire cover and an additional 2" Bumper to bumper coach length. Add 2" for the rear exterior spare tire cover and an additional 2" Bumper to bumper coach length. Add 2" for the rear exterior spare tire cover and an additional 2" Bumper to bumper coach length. Add 2" for the rear exterior spare tire cover and an additional 2" Bumper to bumper coach length. Add 2" for the rear exterior spare tire cover and an additional 2" Bumper to	Electronic ignition water heater.	6	6	6	6	6	6	6	6	6
Approximate exterior unladen coach height from ground to top of roof air. Add 2" to the 26½' models when equipped with the optional 15,000 BTU roof air. NOTE: 23½' models sit higher due to their lighter weight combined with the E-450 chassis. Exterior coach width (add an additional 9" per side for the fold-in cab mirrors). Bumper to bumper coach length. Add 2" for the rear exterior spare tire cover and an additional 2" Bumper to bumper coach length. Add 2" for the rear exterior spare tire cover and an additional 2" Bumper to bumper coach length. Add 2" for the rear exterior spare tire cover and an additional 2" Bumper to bumper coach length. Add 2" for the rear exterior spare tire cover and an additional 2" Bumper to bumper coach length. Add 2" for the rear exterior spare tire cover and an additional 2" Bumper to bumper coach length. Add 2" for the rear exterior spare tire cover and an additional 2" Bumper to bumper coach length. Add 2" for the rear exterior spare tire cover and an additional 2" Bumper to bumper coach length. Add 2" for the rear exterior spare tire cover and an additional 2" Bumper to bumper coach length. Add 2" for the rear exterior spare tire cover and an additional 2" Bumper to bumper coach length. Add 2" for the rear exterior spare tire cover and an additional 2" Bumper to bumper coach length. Add 2" for the rear exterior spare tire cover and an additional 2" Bumper to bumper coach length. Add 2" for the rear exterior spare tire cover and an additional 2" Bumper to bumper coach length. Add 2" for the rear exterior spare tire cover and an additional 2" Bumper to bumper coach length. Add 2" for the rear exterior spare tire cover and an additional 2" Bumper to bumper coach length. Add 2" for the rear exterior spare tire cover and an additional 2" Bumper to bumper coach length. Add 2" for the rear exterior spare tire cover and an additional 2" Bumper to bumper coach length. Add 2" for the rear exterior spare tire cover and an additional 2" bumper to bumper coach length. Add 2"	Propane tank (rated tank capacity).	10	10	10	10	17	17	17	17	17
models when equipped with the optional 15,000 BTU roof air. NOTE: 23½' models sit higher due to their lighter weight combined with the E-450 chassis. Exterior coach width (add an additional 9" per side for the fold-in cab mirrors). Bumper to bumper coach length. Add 2" for the rear exterior spare tire cover and an additional 2" Bumper to bumper coach length. Add 2" for the rear exterior spare tire cover and an additional 2" Bumper to bumper coach length. Add 2" for the rear exterior spare tire cover and an additional 2" Bumper to bumper coach length. Add 2" for the rear exterior spare tire cover and an additional 2" Bumper to bumper coach length. Add 2" for the rear exterior spare tire cover and an additional 2" Bumper to bumper coach length. Add 2" for the rear exterior spare tire cover and an additional 2" Bumper to bumper coach length. Add 2" for the rear exterior spare tire cover and an additional 2" Bumper to bumper coach length. Add 2" for the rear exterior spare tire cover and an additional 2" Bumper to bumper coach length. Add 2" for the rear exterior spare tire cover and an additional 2" Bumper to bumper coach length. Add 2" for the rear exterior spare tire cover and an additional 2" Bumper to bumper coach length. Add 2" for the rear exterior spare tire cover and an additional 2" Bumper to bumper coach length. Add 2" for the rear exterior spare tire cover and an additional 2" Bumper to bumper coach length. Add 2" for the rear exterior spare tire cover and an additional 2" Bumper to bumper coach length. Add 2" for the rear exterior spare tire cover and an additional 2" Bumper to bumper coach length. Add 2" for the rear exterior spare tire cover and an additional 2" Bumper to bumper coach length. Add 2" for the rear exterior spare tire cover and an additional 2" Bumper to bumper coach length. Add 2" for the rear exterior spare tire cover and an additional 2" Bumper to bumper coach length. Add 2" for the rear exterior spare tire cover and an additionale	COACH DIMENSIONS (INCHES)									
Bumper to bumper coach length. Add 2" for the rear exterior spare tire cover and an additional 2" $\frac{1}{8}$	models when equipped with the optional 15,000 BTU roof air. NOTE: 23½ models sit higher due	123	123	123	123	121	121	121	121	124
To the real roof fact today.	· · ·	99	99	99	99	99	99	99	99	99
Interior height from floor to ceiling (excluding carpet). 79 79 79 79 79 79 79 79 79		281	281	281	281	319				368
	Interior height from floor to ceiling (excluding carpet).	79	79	79	79	79	79	79	79	79

FRONT DINETTE FRONT LOUNGE TWIN-KING BED REAR KITCHEN 231/2 REAR LOUNGE BATH 26% ISLAND BED MID BATH COACH SPECIFICATIONS REAR I ISLAND **COACH DIMENSIONS (INCHES)** 261/2 261/2, 1 231/27 261/2' 231/27 231/27 30, 58X80 58X80 58X80 58X80 58X80 58X80 58X80 58X80 Cab-over mattress dimensions. 7X70.7 39X67 39X67. All Dinettes can furnish an eating area for up to 4. The following dinettes can also make into a compact bed. D32 X 71 P36X 76 76 Individual twin bed sizes for models when equipped with twin sofas. The twin sofas can be D34 X 7 P32 X 7 D36X P32X D34X P32X brought completely together, to create an oversize king bed. D = Drivers side. P= Passenger 54X76 54X76 Sofa double bed sizes. 57X78 57X77 Permanent bed size, 261/2' and 30' Island Bed models. 301/2 301/2 33 33 45 38 44 44 4 Total wardrobe hanging space width. COACH MISCELLANEOUS SPECIFICATIONS Total interior recessed fluorescent light fixtures in each floor plan. 4 5 4 4 4 5 5 5 7 7 7 6 9 Total number of interior incandescent light fixtures in each floor plan. 6 6 6 6 6 Total number drawers. 7 7 8 7 8 7 7 8 11 Number of 120V duplex receptacles (including exterior). 5 5 7 5 6 5 5 5 6 Number of roof vents (include escape hatch above cab-over). 3 3 3 3 4 4 4 4 5 Total outside storage compartments. Delete one compartment on the 261/2' Rear Kitchen. 261/2' 2 2 2 5 7 3 5 6 4 Mid-Bath, and 261/2' Rear Bath when equipped with barrel chairs. Triple battery system, including two 6V golf cart batteries in series for coach that produces 12V. 220 220 220 220 220 220 220 Both house batteries together offer the following amp hours, as compared to the industries basic one 12V coach 85-amp battery. **COACH WEIGHTS** WITH FORD V-10 14,050 14,050 ,050 14,050 14,050 14.050 14,050 14,050 G.V.W.R. (Gross Vehicle Weight Rating). Maximum designed motorhome weight when "Fully 4 Loaded". 10,715 10,600 950 10,730 10.650 11,790 970 935 965 E.W. (Empty Weight of Motorhome). No fuels, liquids, supplies or people. (Includes all standard equipment such as generator, etc.) Weights are estimated on some models. ത് o, o, 265 280 11,045 980 300 120 11,060 10,930 U.V.W. - (Unloaded Vehicle Weight). The weight of the motorhome as built at the factory with full 6, fuel, oil, and coolant. Weights are estimated on some models. 5, 6, 5, 5, 7, 10,812 10,744 10,749 10,797 11,617 ,585 ,537 11,404 ,677 W.W.V. - (Wet Weight of Vehicle) No Passengers or supplies. Gas tank, fresh water tank, and LP-Gas tank all full. Weights are estimated on some models. 7, Total number of designated sleeping positions. Delete two sleeping positions when equipped 4 4 2 4 ဖ ဖ ဖ 4 4 with the optional entertainment center. 9 9 S.C.W.R. - (Sleeping Capacity Weight Rating) The number of sleeping positions designated for 9 9 924 9 6 6 61 9 9 each specified floor plan model multiplied by 154 lbs. per person. ,685 *2,483 ,509 ,589 690, ,622 *2,030 C.C.C. - (Cargo Carrying Capacity) Allowable weight available for food, personal items and ,541 *757 supplies. Gas tank, fresh water tank and LP-Gas tank are all full. All sleeping positions Ñ Ñ occupied. NOTE: Installed accessories and towed vehicle tongue weight will reduce C.C.C *This calculation is based on a maximum loaded coach scenario as described in the C.C.C. Your actual carrying capacity will increase with fewer occupants and a reduced carried quantity of fresh water. G.C.W.R. (Gross Combination Weight Rating). Maximum allowable combined weight of "loaded" 20,000 20,000 20,000 20,000 20,000 20,000 20,000 20,000 motorhome and either "loaded tow vehicle or trailer. NOTE: These specifications exceed our coach standard equipped trailer hitch rating. DUE TO CHANGES BY VENDORS COMPONENTS MAY VARY. PRICES AND SPECIFICATIONS ARE SUBJECT TO CHANGE AT ANYTIME WITHOUT PRIOR NOTIFICATION.